


Specifications

Price (US\$ FOB China)	Market	Product Name	Model No.	Issue date
	ASia / Africa / Oceania	OvCamp™ 48AH Battery Hubs	CEHP-48AH24	2019/11/6
Description		Features:		
		<p>MPPT charging, MOSFET protection is adopted between BMS and battery pack, and 10A charging limit is adopted The input is 10A throttling, and the output is Mosfet protected for 15A @DC 24V 'OvCamp™ uses LFP battery cells for energy storage, managed and controlled by industry - proven advanced special purpose battery micro - controller, resulting in maximum performance, safety and longevity of battery pack as well as functional flexibility. OvCamp™ offers intrinsic pure DC output from the battery without any loses or distortion associated with typical voltage regulator. Each ovCamp™ has built-in internal battery management systems, such as capacity, cycle-life tracking, diagnostics, data-logging, as well as, PayGo security encryption timer controls.</p>		
Package Performance (Runtime per solar charge day)		Mechanical		
Energy Throughput:	1229Wh or 48AH@25.6V	Weight:	17.7KG	
Out Max Current:	DC 12V: Port 1+Port 3 =2A Port 2+Port 4 =2A DC24V Interface: 15A	Color:	Black	
USB Max Current:	2x 2A@5V	Battery Box Material:	Metal Parts	
Rated Power:	76W @ DC 12.8V 384W@ DC 25.6V	PAYG:	Enabled	
Output Ports :	4 x DC12V (10-14V) 2 x USB 5V 1xDC S-types Connector 24V	Dimension:	422.2mm*355mm*102mm	
Input Ports:	DC 32-40V	Manufacturers Warranty:	24months warranty, based on the contract date.	
Input Current:	10A	Charging Indicator:	Red LED	
Note: For reference only. Other details please check the related part specification sheets.				
Copyright © 2019 Omnivoltaic Energy Solutions Company Ltd. All rights reserved.				