

Specifications

Price	Markets	Product Name	Model No.	Issue date
	Asia / Africa / Oceania / Americas	24" DC TV	TV24_SRF	11/19/2019



Features:
<ul style="list-style-type: none"> - Specially designed for off-grid usage - Super efficient power consumption - 9-36V wide DC voltage input range - Input voltage polarity reversal protection - Improved picture stability - Multi-media playback options

Panel Specifications	
Display Type	TFT LED
Aspect Ratio	16:9
Resolution	1366*768
Brightness	80nits(optional)
Contrast	1000 : 1
Viewing Angles	85/85/80/80
Maximum Colors	16.7M
Response Time	14ms
Backlight Life	50000 hrs

USB Media			
Media	File Ext	Video	Audio
MOVIE	mpg	MPEG-1, MPEG-2	MP3,PCM,AAC
	avi	Xvid, MJPEG,MPEG-4 SP/ASP,H.263/H.264	
	ts	MPEG-2,H.264,HEVC	
	mov.mkv	MPEG-4 SP/ASP, H.263/H.264, HEVC	
	dat	MPEG-1	
	mp4	MPEG-4 SP/ASP, H.263/H.264, HEVC,MPEG-1/ 2	
	vob	MPEG-2	
MUSIC	mp3		MP3
PHOTO	jpg	Progressive JPEG	
	jpeg	Baseline JPEG	
	bmp	BMP	
	png	Non-Interlaced Interlaced	
SUBTITLE	.srt		
	.ssa/.ass		
	.smi		
	.sub		
	.txt		

FEATURES	
Mainboard	TE.MS3663S.EA67
OSD Languages	English, French, German, Italian, Spanish, Portuguese(optional)
Power to Panel	3.3V,5V,12V
USB Function	Software upgrade,multimedia play

ATV RECEPTION SYSTEM	
Video System	PAL, SECAM,NTSC
Sound System	BG,DK,I,L/L',MN,NICAM / A2
Channels	99CH
Teletext	1000Pages

DTV RECEPTION SYSTEM	
DVB-T	COFDM 2K/8K QPSK,16QAM,64QAM
DVB-S/S2	QPSK,8PSK
DVB-T2	QPSK,16QAM,64QAM,256QAM
DVB-C	16QAM,32QAM,64QAM,128QAM,256QAM
Video Systems	MPEG-2 MP@ML,MPEG-2 MP@HL,H.265,Main/Main-10 profile,@L4.1,Support 8-bit/10-bit color depth,1920*1080@60fps
Sound System	MPEG-1 layer 1/2
Basic Functions	EPG,Subtitle,LCN,Teletext(Eu),MHEG-5(UK)
Max Storage	700 CH (DVB-T+DVB-C)
Channels	3500 CH (DVB-S/S2)

Product Measurement	
Main Unit Including Base	554*165*361 mm
Gross Package	602*125*372mm
N.W/ G.W	2.25/2.8kg
20GP	998
40GP	2030
40HQ	2030

CONNECTORS	
SCART input	1
YPbPr (mini)	1
HDMI input	2
Earphone out	1
CI	1
VGA input(15 pin)	1
Coaxial out	1
CVBS IN (mini)	1
PC audio in	1
USB 2.0	1
DVB-T/C/T2	1
DVB-S/S2	1

POWER REQUIREMENTS	
Input Voltage	DC9-36V
Rated Power	15W
Measured Power	10.4W
Standby Power	0.23W

ACCESSORIES IN THE BOX	
DC Power Cord	1
Remote Control	1
Remote Battery	AAA Batteries x 2
User Manual	1

PATENT	
AC3	Optional
CEC	
HDMI ARC	Optional
MHL2.1	

Note: For reference only. Other details please check the related part specification sheets.
 Copyright © 2019 Omnicore Energy Solutions Company Ltd. All rights reserved.