M400

Overall Performance After One Day Solar Charging (fully charged)

Appliance	Description	Power(W)	Used Alone	Used In Combination(main lamp + secondary lamps)	Run Time Units
Main lighting	1 light points on totaling 200 lumens	1.6	11	5.5	hours
Secondary lamp (2 lamps)	1 secondary lamp on 100 Lumens	0.8	22	5.5	hours
Phone charging	1 typical phone (4wh)				Recommend Phone charging at daytime
Manufacturer			Omnivoltaic Energy Solutions		
Product Series			LUMN		
Model Number			M400(暂定)		
Contact Website			www.omnivoltaic.com		
Warranty			2 year warranty against material or manufacturing defects from purchase, under Normal usage		
Lighting Syste	em		1.011110103090		
Lamp Type			Main lamp with battery		
Main lamp Light Output			200 Lm/100Lm/25Lm		
Light distribution			Color Appearance Warm Daylight Cool (more blue)		
as desk or ceiling light Wide 🕸			Color Rendering (50%) (100%) CRI: 80		
Lamp Type			Secondary lamp without battery		
secondary lamp Light Output			100 Lm/50Lm/25Lm		

Light distribution as desk or ceiling light Wide	Color Appearance Warm Daylight Cool (more blue) Color Rendering (50%) (100%) CRI: 80		
Charging System			
Charge Control	LVD HVD		
Solar Panel	5.5W Poly		
Storage System			
Storage Battery Type	Rechargeable lithium battery		
Battery Capacity	7.2V 2.6Ah		
Battery Protection	Active HVD And LVD		
Easily Replaceable Battery?	Yes		
Special Features			
Cell phone Charging Port	indoor using only		
Drop impact resistant	Rigid Engineering Plastics Mounting Stand		
Torch & remote(Option)	PAYG Ready		